



## **RICO ALPHA SERIES**

## ALPHA 640 50mm

RICO ALPHA SERIES	ALPHA 640 50mm
SENSOR	
Resolution	640x512
Pixel Size	12 μm
Framerate	50hz
Image Processing	MATRIX III
Core	iRay Micro II 640
OPTICS	
Objective Lens	50 mm f/1.1
Magnification	3X
Digital Zoom	4X
FOV	8.8° x 6.6°
Detection Range	2400 Yards
Display Type	AMOLED
Display Resolution	1024x768
Imaging Modes	White Hot, Black Hot, Red Hot, Color, Highlight
Reticle Types	7 (2 Dynamic, 5 Static)
Reticle Colors	Black, White, Red, Green
Mounting System	Picatinny, MIL-STD 1913 / ADM RQD Mount
P.I.P.	Yes
Rangefinder	Stadiametric
Eye Relief	55 mm
Diopter Range	-4 to +4
ELECTRONICS	
Onboard Recording	Video and Image
Wireless Connectivity	Video and Image via App.
Power Supply	Li-Ion Battery Pack
Start Up Time	< 10 Seconds, Instant from Standby
PHYSICAL	
Size	9.84"×2.40"×2.28"
Weight	33.68 ounces
ENVIRONMENTAL/WARRANTY	
Warranty	5 Years
Housing Material	Ultra Rigid, Glass-Filled Polymer
Ingress Protection	IP67
Operation Temp	-4°F~122°F
Max. Recoil	1000 g/s² (300 Win./7mm Mag)

REGISTRATION: irayusa.com/register WARRANTY: irayusa.com/warranty SUPPORT/SERVICE: irayusa.com/support

NOTE: These products may be subject to export and foreign trade control lews of the United States and may not be exported without prior approval of the U.S. Department of State. Learn more at inquisa count/IAR. The thermal images shown are for illustrative purposes only and may vary in real world usage. Specifications are subject to change without notice. For the most up-to-date specs, go to irayusa.com. Not responsible for typographical errors. Ver. 1001/2422







The ALPHA is the product we wanted. Born out of frustration and created based on years of experience from actual use in the field. Designed, machined, and assembled in Texas while being backed by iRayUSA's industry leading 1-week repair guarantee. Want to learn more about what all the excitement is about? Visit irayusa.com/ra50 to see how we have changed the game for you.



